

Advanced Energy Protection

for your household appliances and office equipment



R-AVR3008

Automatic voltage regulator with surge protection

IDEAL PROTECTION FOR



Refrigerators - Photocopiers - Plotters - Washing machine
Multi-Function - Microwave ovens - Printers and more...



R-AVR3008

Automatic voltage regulator with surge protection

DELAY START SYSTEM (30s. 1m. 3m.)



It has a high performance voltage suppressor that absorbs peaks and corrects high and low voltages of electric fluid, the equipment has a delay device of On to protect your appliances (microwaves, refrigerators, and other electronics) as the power supply stabilizes.

Its built-in components filter out harmonic noise that damages electronic logic circuits and protects from spikes and high voltages on telephone and DSL lines.

1. Main OFF/ON button.
2. LED 1 Up - Reduction
3. LED 2 Indicator - Power On
4. LED 3 Down - Boost Increase
5. LED 4 Down - Last / Super Boost Increase
6. Coaxial protection.
7. Breaker.
8. 8 NEMA5-15R and 1 NEMA5-20R outputs regulated and suppressed.
9. Delay device. [30 seg. - 1 min. - 3 min.]

| MODEL | | R-AVR 3008 |
|----------------|---------------------------------------|--|
| Capacity | | 3000VA / 2400W |
| Input | Voltage | 120 Vac |
| | Frequency | 50/60 Hz (automatic) |
| | Voltage range | 50 Vac - 144 Vac |
| | Max. Input Current | 20 Amp. / 2400W |
| Output | Voltage | 90Vac - 135Vac 120Vac |
| | Frequency | 50/60 Hz |
| | Number and type of outputs | 8 NEMA5-15R and 1 NEMA5-20R outputs regulated and suppressed |
| | Max. Output Current | 20 Amp. / 2400W |
| Protections | Delay device | 30 seconds - 1 minute - 3 minutes |
| | Overload | 20 Amp thermomagnetic breaker |
| | Coaxial protection | Integrated coaxial |
| | Lightning Overload Protection(Joules) | 525 |
| LED | (LED 1 Up) | Reducing |
| | (LED 2 Central) | Power On |
| | (LED 3 Down) | Boost Increase |
| | (LED 4 Down) | Last / Super Boost Increase |
| Physical | Dimensions (Length x Height x Depth) | 150 x 150 x 250 mm |
| | Weight (Kg) | 3.86 |
| Environment | Temperature | 0° - 40°C |
| | Acoustic noise | < 40 dB |
| Certifications | | ISO 9001, ISO 14001, CIDET and NOM |

"Specifications subject to change without notice"



Scan and know our products

1120v.1

Bolivia: 800-100156 **Colombia:** 01800-5181617 **Costa Rica:** 800-435237 **El Salvador:** 800-6773 **Honduras:** 1800-25616099
México: 001800 514 8611 **Panamá:** 011-00800-2268611 **Perú:** 0800-54674 **República Dominicana:** 1888-7514876 **Venezuela:** 0800-1627485

