

R-UPR508

Interactive UPS 500VA / 250Watts



R-UPR508 Capacity: 500VA/250W

Interactive UPS with voltage regulators and peak suppressor (No Break) mini-tower design with automatic voltage regulator (AVR), built-in peak suppressor.

It features powerful microprocessor-based controls for greater reliability with automatic voltage regulation. Ideal for protecting computers, network systems and video games.








CHARACTERISTICS:

- 8 Outlets (Nema 5-15R)
4 outputs with backup and AVR.
4 outlets with suppressor.
- 6 USB ports in total:
5 Type-A, 1 Type-C, total of 2.4A.
- Up to 300 Joules of protection against voltage spikes.

PROTECTION:

- Capacity 500VA/250W.
- Peak suppression 300 Joules.
- Voltage range 80-145Vac.
- Overload protection breaker.

TYPICAL APPLICATIONS

- | | | |
|--|--|---|
|  LED/LCD screens |  Video Consoles |  CCTV security systems |
|  Computer System |  Routers/Modem | |
|  Audio/Video and Entertainment |  Points of Sale | |

CERTIFICATIONS



Scan and know
our products



R-UPR₅₀₈

UPS Interactive 500VA / 250Watts



INPUT	
Voltage	120Vac
Frequency	50/60 Hz Automatic adjustment
Voltage range	80 - 145Vac
Max. Input Current (Bypass)	672W (5.6 Max)

OUTPUT	
Voltage	120Vac
Normal battery voltage regulation	120Vac +/- 10%
Frequency	50Hz / 60Hz ± 1Hz
Waveform	Sine Wave Simulation
Transfer time	2-4ms (Typical)
Number and type of outputs	4 with backup and AVR + 4 with suppressor
Maximum Output Current (Bypass)	250W (5.6 max)
USB charger	5 USB-A y 1 USB-C (total 2 amp @ 5Vdc)

BATTERY	
Voltage/Type/Quantity	12VDC 12V/4.5AH * Maintenance free
Recharge time	4 hours at 90% later of the complete download
Security protection	Overload and discharge deep battery


LCD INDICATORS	
Battery mode: 2 short tones every 8 seconds, Low battery: 4 short beeps every second, Overload: Continuous Beep and Buzz, Critical: Continuous Beep	

PROTECTION	
Short circuit protection	Thermomagnetic breaker and Electronic Circuits (Line Mode)
Voltage spike protection (Joules)	300 Joules

PHYSICS	
Dimension (Length x Height x Depth)	195 x 138 x 355 mm
Weight (Kg)	3.55 (Kgs)

The R-UPR series is a line-interactive No-Breaks (UPS) with an integrated wide operating range voltage regulator.

When power flow conditions are normal, the UPS protects you against low and high voltages, while using the power to charge the internal battery.




ON/OFF button and cold start



LED Indicators



5 USB TYPE-A chargers and 1 USB Type-C charger



Breaker

ATMOSPHERE	
Temperature	0° C - 40° C (32°F~104°F)
Relative humidity	0-95% (No Condensed)
Noise level	<40 dB en 1M

CERTIFICACIONES	
NOM, ISO9001- 2015, ISO14001, GCERT Cert. No.: 3166	

"Specifications subject to change without prior notice"

1120v.3



cdpenergy

www.cdpenergy.com