



## UPRS 2008

Sine wave interactive UPS

### IDEAL PROTECTION FOR



Servers, POS equipment, Workstations, Gamers equipment,  
LED / LCD Screens, Computing, Audio / Video, Entertainment and more ...


## UPRS 2008

### Sine wave interactive UPS

The UPRS is an advanced series of interactive line UPSs that produce pure sine wave power for your equipment and for corporate applications that need a higher level of protection.

Its front LCD screen will keep you up-to-date with the conditions of the UPS, while the included software will allow you to program it to carry out specific instructions, such as an operation log, automatic shutdown of the operating system, secure file closing, among others.

The UPRS series provides very short transfer when a power outage occurs, and up to 98% efficiency under normal power conditions.



- 1. LCD screen.
- 2. Power button.
- 3. AC power cable.
- 4. Breaker.
- 5. Fax, modem and DSL protection [RJ11 / RJ45]
- 6. USB communication interface.
- 7. Cooling fan.
- 8. 8 NEMA 5-15R outputs.

MODEL		UPRS 2008
Capacity		2000VA / 1400W
Input	Voltage	120Vac
	Frequency	50/60 Hz +/- 1%
	Voltage range	81 - 145 Vac
Output	Voltage	120Vac
	Voltage regulation battery normal	+/- 10%
	Frequency	50Hz / 60Hz ± 1Hz
	Waveform	Pure sine wave
	Transfer Time	2-4ms (typical)
	Number and type of outputs	8 regulated NEMA5-15R, with battery suppression and backup
Battery	Voltage / Type / Quantity	12V/9Ah x 2
	Recharge time	6 hours recover to 90%
LCD Display	AC Mode, battery mode, load level, battery level, input / output voltage overload, fault y low battery	
Alarm	Battery mode: 1 beep every 10 seconds, Low battery: 1 beep every second, Overload: 1 beep every half second, Battery replacement: 1 beep every 2 seconds, Failure: 1 continuous beep	
Protection	Safety Protection	Overcharge, discharge and overcharge
Communication interface		USB
Physical	Dimensions (Length x Height x Depth)	397 x 146 x 205 mm
	Net. Weight (kgs)	13,7 Kg
Environment	Temperature	0° C - 40° C (32°F~104°F)
	Humidity	0-90% (non condensed)
	Acoustic Noise	<55 dB 1M
Certifications	NOM, ISO9001- 2015, ISO14001, CIDET	
Software	Management via USB / RS-232 port	Supporting Windows 98/NT/2000/Me/XP/2003/Vista/7/8/10

"Specifications subject to change without notice"



Scan and know our products

**Bolivia:** 800-100156 **Colombia:** 01800-5181617 **Costa Rica:** 800-435237 **El Salvador:** 800-6773 **Honduras:** 1800-25616099  
**México:** 001800 514 8611 **Panamá:** 011-00800-2268611 **Perú:** 0800-54674 **República Dominicana:** 1888-7514876 **Venezuela:** 0800-1627485